
PŘÍLOŽNÝ TERMOSTAT TS53

10746


TS53 je termostat teploty vody, určený k montáži na trubku (TS5310) nebo na zásobník TV (TS5320).
Je zejména vhodný k regulaci teplé vody v obytných i průmyslových zařízeních.

Rozměry



Technické a elektrické údaje

Rozsah regulace: 17-90 °C
Zatížení kontaktů: C-1 16(2,5)A/250 V~
C-2 3(1)A/250 V~
Min. proud: 200 mA
Připojení kabelů do svorkovnice
El. krytí: IP 40
Teplotní diference: asi 10 °C
Vnitřní bimetalový termostat Ty53, schválen VDE/UL
Hmotnost: 120 g
Termostat je zařízení třídy II (zařízení s dvojitou izolací), které nevyžaduje uzemnění.




Verze TS5310

Vhodný k montáži na trubku pomocí pružiny příchytky (obr. 1).

min. průměr trubky = 27 mm -- 3/4“
max. průměr trubky = 115 mm -- 4“

Obr. 1



Verze TS5320


Vhodný k montáži na zásobník TV pomocí pružiny (obr. 2).

Návod na montáž:

Odměřte si vhodnou délku pružiny, případně ji zkraťte, aby byla stále napnutá. Na její konce nasaďte háčky.
Zapojte termostat elektricky: Tuto operaci musí provést osoba odborně způsobilá (obr. 4).
Namontujte termostat na zásobník TV podle obr. 2 a zasuňte ho pod pružinu tak, aby zapadla do příslušného zářezu v krytu (obr. 3).




Obr. 2




Obr. 3

Svorkovnice



Obr. 4



Výrobce: CAMPINI COREL

Distributor: Regulus

Termoregolatori Campini Corel S.p.A.
22066 Mariano Comense - Como - Italy
Via Don Guanella, 1


Regulus spol. s r.o.
Do koutů 1897/3, 143 00 Praha 4
Tel.: 241 764 506 Fax: 241 763 971
e-mail: obchod@regulus.cz, www.regulus.cz

CE

CONTACT THERMOREGULATOR TS53


The TS53 is a water temperature thermoregulator designed for surface mounting on water pipes (TS5310) or domestic hot water cylinders (TS5320). It is particularly suitable for the water temperature regulation in civil and industrial thermic installations.

Dimensions



Technical and electric features

Control range : 17° ÷ 90°C
Breaking capacity: C-1 16(2.5)A/250V~
C-2 3(1)A/250V~
Minimun current: 200 mA
Cable fastening by terminal board
Protection level: IP 40
Differential: approx.10°C
Internal Ty53 bimetallic thermoregulator VDE/UL approved.
Weight: 120 gr.
The thermostat is a class II (double insulated device) requiring no earth connection.



Version TS5310

Suitable for surface mounting on water pipe by means of a spring clip (fig.1).

ø min. pipe = 27mm -- 3/4'
ø max. pipe = 115mm -- 4'




Fig.1

Version TS5320

Suitable for surface on domestic hot water cylinder by means of a spring wire (Fig.2).

Fixing instructions:

Determine the correct length of the spring wire and cut it if necessary to ensure it is under slight tension.
Fit the two hooks on the ends of the spring wire.
Wire the thermostat: this operation should be carried out by a competent electrician in accordance with the appropriate IEE wiring regulations (fig.4).
Mount the thermostat on the hot water cylinder as shown in fig.2 and fit it under the spring wire ensuring that the wire fits in the appropriate slot on the cover (fig.3).




Fig.2






Fig.3

Wiring terminals





Producer: CAMPINI COREL

Distributor: Regulus

Termoregolatori Campini Corel S.p.A.
22066 Mariano Comense - Como - Italy
Via Don Guanella, 1

Regulus spol. s r.o. Czech Republic
Do koutù 1897/3, 143 00 Praha 4
Tel.: ++420 241 765 191 Fax: ++420 241 763 976
e-mail: sales@regulus.cz, www.regulus.eu

CE